

The ADA range of flashing arrows is designed to provide advance warning and directional information for the temporary diversion of vehicular traffic.

The arrows meet the requirements of Australian standard AS/NZS 4192:2006 and are approved by the NSW Roads & Traffic Authority (FAS 5) and are suitable for use in all Australian states.



Small easy to use controller with LED indicators

Double Sided Single Sided



Single Sided specifications

Specifications

Type A

Type B

Size	1250mm x 650 mm	1500mm x 750 mm
Weight	45 kg	50kg
Number of LED Clusters	13	15
Standard visibility	500 metres	860 metres
Normal use	Urban-Rural roads	Urban-Rural-Free Way
Material-Frame	Aluminium 3mm	Aluminium 3mm
Arrow Front & Back	Aluminium 2mm	Aluminium 2mm
Finish	Powdercoated Black	Powdercoated Black
LED Type - High Performance	ADA 38	ADA 38
InCab Controller	110mm x 60mm	110mm x 60mm
Control cable - standard	6 (six) metres	8 (eight) metres



Optional light bar available as shown here mounted below main signal display.

Features

- FAS-5 RTA approval certificate 0807-FAS5-0-1A & B
- Independently tested to comply with Australian Standard AS4192-2006
- Actuator lift standard - fixed installation available
- Heavy duty Aluminum construction
- Small Incab controller with LED real time display indicates whether arrow is up or down and which mode is showing
- Low and High voltage protection with automatic switch to warning mode
- Automatic dimming with inbuilt light detector
- Australia Communications Authority - C Tick
- Operates as 12 or 24 volt without need for reducer
- LED clusters easily replaced
- LED clusters can be retrofitted to most existing globe based arrow boards
- Backed by 100% parts coverage with local field service available

Options

- Side arms and base available in Aluminium
- Manual side arms for fixed installations
- Custom length control cable
- Available in double sided - NOVA or ADA
- Optional light bar (as shown above)
- Onsite installation available



Manufactured in Australia by
Australian Directional Arrows



Australian Directional Arrows

- Multi voltage - 12 & 24 Volt
- Real Time LED Display
- Single & Double sided
- RTA FAS 5 Approved
- AS4192-2006 Approved

Distributed by

Traffic Signal Sales & Service Pty Ltd - NSW
 mobile: 0419 971 680
 phone: 02 9655 1307
 fax: 02 4782 7572
 web: www.trafficsignals.com.au
 email: trafficsignals@pnc.com.au



VWS Pty Ltd - Victoria, Queensland, South Australia
 mobile: 0406 383 106
 phone: 1300 897287
 fax: 1300897327
 email: pfoley@vwsa.com.au



Australian Directional Arrows